# VAISALA

## HM70 Hand-held Humidity and Temperature Meter

| | | HM70 | | | | | | | | | PRICE |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Indicator type | no indicator * | A | | | | | | | | | |
| | rechargeable with Euro AC-adapter | B | | | | | | | | | |
| | rechargeable with UK AC-adapter | C | | | | | | | | | |
| | rechargeable with US AC-adapter | D | | | | | | | | | |
| | rechargeable with AUS AC-adapter | E | | | | | | | | | |
| | rechargeable with all AC-adapters | F | | | | | | | | | |
| | alkaline batteries only | K | | | | | | | | | |
| Indicator accessories | **no indicator accessories** | | 0 | | | | | | | | |
| | *MI70LINK software with RS232 cable (MI70LINK)* | | 1 | | | | | | | | |
| | *analog output-signal cable (27168ZZ)* | | 2 | | | | | | | | |
| | *MI70Link with RS232 and analog output signal cables* | | 3 | | | | | | | | |
| | *MI70LINK software with USB cable (219687)* | | 4 | | | | | | | | |
| Probe type | *HMP75* | | | A | | | | | | | |
| | *HMP75B (chemical purge and sensor preheating)* | | | F | | | | | | | |
| | *HMP76* | | | B | | | | | | | |
| | *HMP76B (chemical purge and sensor preheating)* | | | C | | | | | | | |
| | *HMP77* | | | D | | | | | | | |
| | *HMP77B (chemical purge and sensor preheating)* | | | E | | | | | | | |
| Calibration | **at room temperature** | | | | 1 | | | | | | |
| Probe accessories | **no accessories** | | | | | A | | | | | |
| | *probe holder for HMP76/76B \*\** | | | | | B | | | | | |
| Connection cable to a transmitter | **no connection cable** | | | | | | 0 | | | | |
| | *connection cable to HMD/W60/70 series (HMA6070)* | | | | | | 1 | | | | |
| | *connection cable to HMP230 series / HMP228 (27159ZZ)* | | | | | | 2 | | | | |
| | *connection cable to 20/30 series transmitters (HMA2030)* | | | | | | 3 | | | | |
| | *connection cable to HMT330 and HMT120/130 (211339)* | | | | | | 4 | | | | |
| | *connection cable to HMW90 (219980)* | | | | | | 6 | | | | |
| Carrying case | **no carrying case** | | | | | | | A | | | |
| | *weather proof carrying case for MI70 and probe (HMP75/77/77B) (MI70CASE3)* | | | | | | | D | | | |
| | *weather proof carrying case for MI70 and long probe (HMP76/76B) (MI70CASE4)* | | | | | | | E | | | |
| Manual language | **No manual** | | | | | | | | A | | |
| | **English** | | | | | | | | B | | |
| | | | | | | | | | TOTAL | | |
| | | | | | | | | | QTY | | |
| | | | | | | | | | TOTAL VALUE | | |

\* select item A, if only probe is ordered
\*\* used in field calibration of duct 60/70 and 20/30 transmitters
\*\*\* aluminium case for HMP76 probe (long case)

**Selections in bold are included in the prices of the basic versions.**
*Selections in italic are available at an extra price.*

Example of order code with typical settings:

| HM70 | B | 4 | A | 1 | A | 0 | D | B |
|------|---|---|---|---|---|---|---|---|

End customer: _____

| *Accessories:* | *Order code:* |
|---|---|
| *Connection cable to HMT330 and HMT120/130* | *211339* |
| *Connection cable to HMT310* | *DRW216050* |
| *Connection cable to HMD/W60/70 series* | *HMA6070* |
| *Connection cable to HMW90* | *219980* |
| *Weather proof carrying case for MI70 and short probe* | *MI70CASE3* |
| *Weather proof carrying case for MI70 and long probe* | *MI70CASE4* |
| *MI70LINK software with USB cable* | *219687* |
| *MI70LINK software with serial port cable* | *MI70LINK* |
| *Analog output cable* | *27168ZZ* |